

PRODUCT INFORMATION CARD - CUBEx IS LIGHTS VARIATIONS

LIGHTS	MOLEX CONNECTOR	AMPHENOL MALE (Pigtail)	APPLICATIONS	DESCRIPTION	MAX DC CURRENT CONSUMPTION AT 12V and T _a = 25°C (mA)
	CX300-001	CX302-001	Ambient	IS Light, Ambient, 6xWhite 60 Deg	655
	CX300-004	CX302-004	Reverse Tail	IS Light, Reverse/Ambient+Tail, 4xWhite, 2xRed, 6x60 Deg	457
	CX200-006	CX302-006	Remote/Injury	IS Light, Remote/Injury, Blue Antiphase Flashing (630mHz), 2xDNP, 4x60 Deg	390
	CX300-009	CX302-009	TAIL + Spotlight	IS Light, 4xWhite 5 Deg, 2xRed 60 Deg	457
	CX300-009-MAX	CX302-009-MAX	TAIL + Spotlight	IS Light, 4xWhite 5 Deg, 2xRed 60 Deg, White Maximum Brightness (50% more than CX30X-009)	1216
	CX200-011	CX302-011	Traffic	IS Light, 2xRed, 2xYellow, 2xGreen, 6x60 Deg, Green 10% Brightness	142
		CX302-015	BSL	IS Light, BSL, 4xRed, 2xWhite, 6x60 Deg	1022
	CX200-017	CX302-017	Mode	IS Light, Mode Lights, 2xRed, 2xYellow, 2xGreen, 6x60 Deg, Maximum Brightness	799
		CX302-021	Flashing Green	IS Light, Flashing Green (750mHz), 6xGreen 60 Deg	176
		CX302-022	Green Red Status	IS Light, 4xGreen, 2xRed, 6x60 Deg, Maximum Brightness	651
		CX302-023	Hazard/Solid Red	IS Light, 6xRed 60 Deg, Maximum Brightness	993
	CX200-028	CX302-028	Emergency Hazard	IS Light, Yellow, 2xDNP, 4x60 Deg, 4mA per Bank	8
		CX302-029	Cutthrough/Awaren ess	IS Light, 4xWhite, 2xGreen, 6x60 Deg	558
		CX302-030	Ambient Hazard	IS Light, Ambient, 4xWhite 5 Deg, 2xYellow Flashing (630mHz) 60 Deg, White High Brightness	1118
	CX300-050	CX302-050	Ambient	IS Light, Ambient, 6xWhite 60 Deg, 80% Brightness	525
		CX302-051	Ambient	IS Light, Ambient, 6xWhite 60 Deg, 65% Brightness, V _{min} = 8.5V	422
	CX300-052		Green Signal Light	IS Light, Green, 2xDNP, 4x60 Deg, 4mA per Bank	8
	CX300-053		Ambient	IS Light, White, 4x60 Deg, 90% Brightness, 2x60 Deg, 10% Brightness	405
	CX300-101	CX302-101 CX302-101-TW	Ambient	IS Light, Ambient, 6xWhite 60 Deg, 90% Brightness IS Light, Ambient, 6xWhite 60 Deg, 90% Brightness, Two-Wire	580



AMPHENOL PIGTAIL



MOLEX CONNECTOR



