

Reliable underground communications using pilot or power cores

Powerful Broadband Powerline Modem (BPLM) range promotes assisted automation and improved mining operations in complex environments underground

- ✓ Power, powerline comms and remote displays
- ✓ 2 WIFI ports for up to 5 client devices
- ✓ 4 Ethernet ports
- ✓ Built in diagnostic functionality
- ✓ Daisy chain BPLM 2.0 for network extension
- ✓ Assign IP addresses for network configuration

Suitable for
Hardrock and
Softrock



Creates a reliable network connection across multiple machines in order to transmit data between equipment and the surface

NETWORK TECHNOLOGY

Network challenges in underground mining include confined spaces, lack of GPS, explosive atmosphere, weak strata and complex mining machinery. As such, use of powerline for communications is best for underground, tethered vehicles.

Network	Open Cut	Underground Hard Rock	Underground Soft Rock
Wide Areas	●		
Confined Spaces		●	●
No GPS		●	●
Chemical Attack		●	●
Explosive Atmosphere			●
Weak Strata			●
Complex Mining Machinery			●


Technology	Ethernet	Fibre	Radio	Powerline
Data Rate		Best		
Distance	Worst	Best		
Environmental Survival		Worst		Best
Drop-Outs			Worst	
Infrastructure Burden				Best
Mobile			Best	

Harnessing Technology to Keep Miners Safe


NAUTITECH® is an Original Technology Manufacturer (OTM) and global provider of smart electronic and software solutions for OEMs and mine sites in underground mining.

We design and manufacture equipment that delivers **Communications and Visibility**, supports **Automation**, and provides a platform for **Asset and Condition Monitoring** of underground equipment. Our **DataMaster data analytics** software can help detect safety risks and gain intelligence for improved mining operations.

SOFT ROCK MINING





HARD ROCK MINING




Environmental Specifications

Supply voltage (Hardrock)	20 to 28 VAC
Supply Voltage (Softrock)	85 to 264 VAC
Supply frequency	50 Hz, 60 Hz
Supply power, max	12 W
Ethernet interface	10BASE - T/100BASE-TX Shielded RJ45
Operating temperature	0° to 60°C
Vibration	IEC 60068-2-6
Shock	IEC 60068-2-27
EMC emissions	IEC 61000-6-4
EMC immunity	IEC 61000-4-2/3/4/5/6/8




CAPACITIVE COUPLER



SPITFIRE[®]

Bidirectional TCP Traffic vs Simulated Powerline Attenuation



BPLM 2.0



BPLM



Super Spitfire



Wingman

Scan QR Code to watch the Spitfire in action

- ✓ Real-time System Data
- ✓ Productivity Analysis
- ✓ Voice and Video
- ✓ Monitoring

